

U/UTP 4Pairs cable-category 6- PVC Sheath

Content of the Data Sheet					
Sheath Printing	HIKVISION E484059-Z (UL) CM 4PR 23AWG 75 °C U/UTP CAT6 VERIFIED TO ANSI/TIA-568-C.2 PVC ****m mm/dd/yyyy				
Customer Reference	DS-1LN6-UU				
Category	U/UTP CAT6-4P-PVC-CM				
Reference Standard	ISO/IEC11801、TIA-568-C.2、UL444				
Conductor	Material	SOLID-Bare Copper			
	Content	99.95%			
	Nom.O.D.(mm)	0.565 (23AWG)	up	+0.005	
			down	-0.005	
Insulation	Material	HDPE			
	Diameter	1.02±0.05mm			
Sheath	Thickness	0.55±0.05 mm			
	External O.D.	6.2±0.4 mm			
	Surface	Clean,Frap,Satiation			
	Material	PVC(complies RoHS),CM			
	Color	Orange RAL2003			
Surface Printing	Letter height	3.0±0.3mm			
	Color	Black			
	Print error & Space	≤±0.5%, 1m			
Core Color	1 White- Blue /Blue	2 White-Orange /Orange			
	3 White-Green /Green	4 White- Brown /Brown			
Packing	Wooden Tray & Carton				
Carton dimension	Per request				
Packing length	305±1.5m				
Rip-cord	Yes	Drain wire	No		
Sheath Physical Properties	Before Aging Tensile Strength (Mpa)	≥13.5			
	Elongation(%)	≥150			
	Aging Period (°C×hrs)	100°C×24h×10d			
	After Aging Tensile Strength(Mpa)	≥12.5			
	Elongation(%)	≥125			
Electrical Characteristics (20°C)	1.0-250.0MHz Impedance ((Ω)	100±15			
	1.0-250.0MHz Delay Skew (ns/100m)	≤45			
	DC Resistance (Ω/100m) max	9.38			
	DC Conductor Resistance Unbalance (%) max	5.0			
Technical Performance (100m):					
	Frequency (MHz)	RL ≥dB	ATT (20°C) ≤dB	NEXT ≥dB	PHASE DELAY ≤ns
	1	20.0	2.03	74.3	570.00
	4.0	23.0	3.78	65.3	552.00
	8.0	24.5	5.32	60.8	546.73
	10.0	25.0	5.95	59.3	545.38
	16.0	25.0	7.55	56.2	543.00
	20.0	25.0	8.47	54.8	542.05
	25.0	24.3	9.51	53.3	541.20
	31.25	23.6	10.67	51.9	540.44
	62.5	21.5	15.38	47.7	538.55
	100	20.1	19.80	44.3	537.60
	200	18.0	28.98	39.8	536.54
	250	17.3	32.85	38.3	536.27
	Frequency (MHz)	PSNEXT ≥dB	ELFEXT ≥dB	PSELFEXT ≥dB	
	1	72.3	67.8	64.8	
	4	63.3	55.8	52.8	
	8	58.8	49.7	46.7	
	10	57.3	47.8	44.8	
	16	54.2	43.7	40.7	
	20	52.8	41.8	38.8	
	25	51.3	39.8	36.8	
	31.25	49.9	37.9	34.9	
	62.5	45.4	31.9	28.9	
	100	42.3	27.8	24.8	
	200	37.8	21.8	18.8	
	250	36.3	19.8	16.8	
Ambient temperature: -20°C - 75°C			Operating Voltage: 80V		

