



HIKVISION

DS-3K01-17S is used for multiple optical receiver (like DS-3D01R-AU) management, the whole system is capable of transmitting optical signal via the Ethernet Interface in the single-fiber and single-mode, and can be used both in pairs and cooperated with 100M Optical Transceiver. Owing to the industrial design which is highly reliable, DS-3K01-17S can be widely applied to the video surveillance systems in public security, transportation, mine, factory, etc.

Available model: DS-3K01-17S


Key Features

- 19 inch width, 4U height
- Dual power supply design, each 220V AC
- 17 usable receiver chassis
- Backboard support VMS signal transmission
- Aluminum structure





Dimensions



Distributed by

L

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com Hikvision Europe T +31-23-5542770 saleseuro@hikvision.com

Hikvision France T +33(0)1-85-330-444 info.fr@hikvision.com

Hikvision Oceania T +61-2-8599-4233 salesau@hikvision.com Hikvision Middle East T +971-4-8816086 salesme@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Hong Kong T +852-2151-1761 Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Poland T +48-22-460-01-50 poland@hikvision.com

Hikvision Canada T +1-909-895-0400 sales.usa@hikvision.com Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision UK T +44-1628-9021-4 support.uk@hikvision.com

© Hikvision Digital Technology Co., Ltd. 2016 | Data subject to change without notice |