

## DS-D2046NH-E LCD Display



The DS-D2046NH-E LCD display uses an industry-level extreme-narrow bezel design, which enables a bezel width of 1.7 mm between neighboring displays. The adopted direct-lit LED backlighting technology helps achieve ultra-high and uniform brightness of 700 cd/m<sup>2</sup> without boundary shadows. The display has abundant interfaces for video inputs, such as DVI, VGA, and HDMI.


- Direct-lit LED backlight with uniform brightness and no boundary shadows
- 1920 × 1080 resolution, 178° viewing angle
- Extreme narrow 1.7mm bezel design
- Factory calibration for color uniformity
- Anti-glare, high definition, high brightness, high color gamut, and vivid images with rich colors
- Stable and 24-hour continuous working
- Metal casing for preventing from radiation and magnetic & electric field interference
- Wall-mount and modular brackets available to meet various installation requirements



## ▪ Specification

Model		DS-D2046NH-E
<b>Product Model</b>	Product Model	DS-D2046NH-E
<b>Display</b>	Screen Size	46 inch
	Active Display Area	1018.08 (H) mm × 572.67 (V) mm
	Backlight	Direct-lit LED backlight
	Pixel Pitch	0.53 mm
	Physical Seam	1.7 mm
	Bezel Width	1.1 mm (top/left), 0.6 mm (bottom/right)
	Resolution	1920 × 1080@60 Hz (downward compatible)
	Brightness	700 cd/m <sup>2</sup>
	Viewing Angle	Horizontal 178°, vertical 178°
	Color Depth	8 bit, 16.7 M
	Contrast Ratio	4000:1
	Response Time	8 ms (G to G)
	Color Gamut	72% NTSC
	Surface Treatment	Haze 25%, 2H
<b>Interface</b>	Video & Audio Input	HDMI × 1, DVI × 1, VGA × 1, CVBS × 1, USB × 1
	Video & Audio Output	DVI × 1, VGA × 1, CVBS × 1
	Control Interface	RS232 IN × 1, RS232 OUT × 1
<b>Power</b>	Power Supply	100-240 VAC, 50/60 Hz
	Power Consumption	≤ 139 W
	Standby Consumption	≤ 0.5 W
<b>Working Environment</b>	Working Temperature	0°C to 40°C (32°F to 104°F)
	Working Humidity	20% to 90% RH (non-condensing)
	Storage Temperature	-20°C to 65°C (-4°F to 149°F)
	Storage Humidity	5% to 90% RH (non-condensing)
<b>General</b>	Casing Material	SECC
	VESA	600 (H) mm × 400 (V) mm
	Product Dimension (W × H × D)	1020.02 mm × 574.61 mm × 71 mm (40.22" × 22.62" × 2.8")
	Package Dimension (W × H × D)	Carton with two displays: 1214 mm × 783 mm × 414 mm (47.8" × 30.83" × 16.3") Carton with a single display: 1214 mm × 783 mm × 414 mm (47.8" × 30.83" × 16.3")
	Net Weight	19.24 ± 0.5 Kg (42.42 ± 1.1 lb) for single display
	Gross Weight	Carton with two displays: 47.68 ± 0.5 Kg (105.12 ± 1.1 lb) Carton with a single display: 26.07 ± 0.5 Kg (57.47 ± 1.1 lb)
	Packing List	LCD display × 1, power cable × 1, network cable × 1, screw × 4, installation instruction × 1, remote control × 1, IR receiver × 1, CD-ROM × 1, RS-232 converter × 1


## ▪ Physical Interface



Interface	Description	Interface	Description
POWER	Power indicator	HDMI IN	HDMI input interface
DVI OUT	DVI-I output interface for digital signals	DVI IN	DVI-I input interface for digital signals
VGA OUT	VGA output interface for analog signals	VGA IN	VGA input interface for analog signals
CVBS OUT	CVBS output interface for signals	CVBS IN	CVBS input interface for signals

USB	USB interface	RS232 IN	Serial loopback input interface
RS232 OUT	Serial loopback output interface	IR IN	IR input interface

## Dimension



## Available Model

DS-D2046NH-E

Distributed by



## HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com